



深圳市永连旺电子有限公司

Shenzhen Yonglianwang Electronic CO.,LTD.

1.27mm Board Spacer, Dual Row, Straight/Right Angle

SPECIFICATIONS

Current Rating : 1AMP
 Operation Temperature: -40° C to +105° C
 Contact Resistance : 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: Nylon-6T
 Contact Material : Brass
 Contact plating : Au or Sn Over 50u² Ni



PCB LAYOUT

Ordering Information

1 3 15 — 2 2 XX	G0	S	XXX 01
Plastics Height 10=1.0mm 15=1.5mm	Contact Plating SN : Tin G0 : Gold Flash G2 : 5u" Gold G3 : 10u" Gold G4 : 15u" Gold G5 : 30u" Gold S0 : Gold Flash/Tin Standard: G0	Connector Type S=Straight R=Right Angle	Pin Length XXX=A+B+C XXX=A+D+C+B+1.06
No. of Pins Per Row 01~50			

Tel : 86-0755-27367782

Fax : 86-0755-27382610

Http://www.szyLconn.com

E-mail:sales@szyLconn.com

地址:广东省深圳市宝安区福永街道兴围第一工业区兴华路北第17幢