







# 深圳市永连旺电子有限公司

## Shenzhen Yonglianwang Electronic CO.,LTD.

### 1. 00mm Female Header, Dual Row, S. M. T

#### SPECIFICATIONS

Current Rating : 0.75AMP  
 Operation Temperature: -40° C to +105° C  
 Contact Resistance : 30mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage : AC 500V  
 Insulator Material : High Temperature Thermoplastic (UL94V-0)  
 Contact Material : Phosphor Bronze  
 Contact plating : Au over 50 u<sup>2</sup> Ni



#### PCB LAYOUT

#### Ordering Information

2 5 21 — 2	<u>XX</u>	M	<u>G0</u>	<u>C</u>	U N 01
No. of Pins Per Row 03~50	Contact Plating G0 : Gold Flash G2 : 5u <sup>2</sup> Gold G3 : 10u <sup>2</sup> Gold G4 : 15u <sup>2</sup> Gold G5 : 30u <sup>2</sup> Gold S0 : Gold Flash/Tin Standard: G0	Material Type C: Nylon-6T D: LCP B: Nylon-46			

Tel : 86-0755-27367782

Fax : 86-0755-27382610

Http://www.szyLconn.com

E-mail: sales@szyLconn.com

地址: 广东省深圳市宝安区福永街道兴围第一工业区兴华路北第17幢