

NOTES


- MATERIALS  
 COVER: PPS UL94V-0  
 HOUSING: LCP UL94V-0  
 CONTACT: PHOSPHOR BRONZE.  
 LATCH: PHOSPHOR BRONZE
- FINISH  
 CONTACT: 1. TIN/LEAD  
 90/10, 120u"  
 LATCH: TIN/LEAD  
 90/10, 120u"
- SPECIFICATION  
 VOLTAGE RATING: 50V  
 CURRENT RATING: 50V  
 CONTACT RESISTANCE: 20M OHM MIN  
 INSULATION RESISTANCE: 100M OHM MIN  
 TEMPERATURE RANGE: -20° TO 85° C.

1. THIS PRODUCT IS LOWER CONTACT TYPE CONNECTOR. IN THE PACKAGE ACTUATOR SHOULD BE LOCKED.

P. NO	A	B	C	D	E
3P	6.95	1.00	5.85	6.65	2.00
4P	7.45	1.50	6.35	7.15	2.50
5P	7.95	2.00	6.85	7.65	3.00
6P	8.45	2.50	7.35	8.15	3.50
7P	8.95	3.00	7.85	8.65	4.00
8P	9.45	3.50	8.35	9.15	4.50
9P	9.95	4.00	8.85	9.65	5.00
10P	10.45	4.50	9.35	10.15	5.50
11P	10.95	5.00	9.85	10.65	6.00
12P	11.45	5.50	10.35	11.15	6.50
13P	11.95	6.00	10.85	11.65	7.00
14P	12.45	6.50	11.35	12.15	7.50
15P	12.95	7.00	11.85	12.65	8.00
16P	13.45	7.50	12.35	13.15	8.50
17P	13.95	8.00	12.85	13.65	9.00
18P	14.45	8.50	13.35	14.15	9.50
19P	14.95	9.00	13.85	14.65	10.0
20P	15.45	9.50	14.35	15.15	10.5
21P	15.95	10.0	14.85	15.65	11.0
22P	16.45	10.5	15.35	16.15	11.5
23P	16.95	11.0	15.85	16.65	12.0
24P	17.45	11.5	16.35	17.15	12.5
25P	17.95	12.0	16.85	17.65	13.0
26P	18.45	12.5	17.35	18.15	13.5
27P	18.95	13.0	17.85	18.65	14.0
28P	19.30	13.5	17.35	18.05	14.5
29P	19.95	14.0	18.85	19.65	15.0
30P	20.45	14.5	19.35	20.15	15.5
31P	20.95	15.0	19.85	20.65	16.0
32P	21.45	15.5	20.35	21.15	16.5
33P	21.95	16.0	20.85	21.65	17.0
34P	22.45	16.5	21.35	22.15	17.5
35P	22.95	17.0	21.85	22.65	18.0
36P	23.45	17.5	22.35	23.15	18.5
37P	23.95	18.0	22.85	23.65	19.0
38P	24.45	18.5	23.35	24.15	19.5
39P	24.95	19.0	23.85	24.65	20.0
40P	25.45	19.5	24.35	25.15	20.5
41P	25.95	20.0	24.85	25.65	21.0
42P	26.45	20.5	25.35	26.15	21.5
43P	26.95	21.0	25.85	26.65	22.0
44P	27.45	21.5	26.35	27.15	22.5
45P	27.95	22.0	26.85	27.65	23.0
46P	28.45	22.5	27.35	28.15	23.5
47P	28.95	23.0	27.85	28.65	24.0
48P	29.45	23.5	28.35	29.15	24.5
49P	29.95	24.0	28.85	29.65	25.0
50P	30.45	24.5	29.35	30.15	25.5

深圳市永连旺电子有限公司

FPC PITCH 0.5mm				
Customer:	Approval:	Unit	Scale	Date
Drawing:	Check:	mm		02.10.23



P NO:
Pin Longer:
Signatuer: